

item number	diameter (mm)	weight 100 pcs (kg)	packing (pcs)
5208 D_ZNCR	8	1,11	50
5210 D_ZNCR	10	1,12	50
5212 D_ZNCR	12	1,15	50
5216 D_ZNCR	16	1,23	50
5220 D_ZNCR	20	1,33	50
5225 D_ZNCR	25	1,62	50
5232 D_ZNCR	32	1,79	50
5240 D_ZNCR	40	2,29	50
5250 D_ZNCR	50	2,92	25
5263 D_ZNCR	63	7,12	25



product description: DOBRMAN clamps are used to fasten cables or pipes to base material to create standardized or non-standardized cable trays with maintained functionality during fires.

The clamps are attached to base material using KPO 6 anchor, SVD screw or ZT 6 threaded rod and KPOZ 6 anchor. Max. fastening spacing is 600 mm for non-standardized trays. It's 300 mm for standardized cable trays.

On the clamps is thread M6 for fixing.

To facilitate installation the clamp is provided with a groove for insertion; it is not necessary to separate completely the top part of the clamp at the installation.

maximum load: max. 3 cables in one clamp

surface finish: ZNCR - galvanized steel

sales amount: á 1 pc

classification: ČSN 73 0895 P 90-R
DIN 4102-12 E 90
STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

storage: EN 60721-3-1

