

type number: **QS 45X45 C**

item number: QS 45X45 C_HB - white
 QS 45X45 C_BB - red
 QS 45X45 C_FB - black

for wires: 1,5-2,5 mm² Cu
 fasten the wire: with screws
 rated voltage: 250 V AC
 rated current: 16 A
 IP-protection: IP20
 material: PC - ABS
 dimension (width x height): 45 x 45 mm
 dimension (depth): 40 mm
 weight: 39 g/pc

certification: ČSN IEC 60884-1
 storage: ČSN 64 0090

installation: by click only
 sockets can be connect continuously, trunkings or boxes determine max.number of sockets
 recommended tightening torque 0,6 Nm

suitable for: parapet trunkings
 PK 90X55 D, PK 120X55 D, PK 160X65 D, PK 170X65 D, PK 210X70 D
 floor boxes
 KOPOBOX 57, KOPOBOX 80
 multi-purpose boxes
 KOPOBOX mini
 instrument carrier
 QUADRO PNQ

description: the shutters physically block access to live contacts and only allow the plug to be inserted
 when even pressure is applied to both openings at the same time



recycling codes:



plastic parts of the socket



other parts of the socket



carton



foil

Warning: Incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person.

Product damage - if the socket module is visibly damaged, stop using it.

Follow the manufacturer's installation instructions according to the installation instructions, videos.

Under normal and foreseeable conditions of use, the installed socket module does not pose any risks to consumers.